

# CXT400 Specifications



## Description

The EAW CXT line of ceiling speakers is a cost effective professional set of ceiling speakers that can provide solutions for high quality sound and install friendly features for applications requiring mid-volume music playback and paging.

The EAW CXT400 is a full-range 4" coaxial, ported ceiling speaker that provides premium performance and wide dispersion in a simple blind mount installation package. The coaxial design pairs a 4" LF and .75" soft dome tweeter for a coherent 120-degree conical dispersion, 100Hz-20kHz response, handling 60W and delivering a 108dB Max-SPL. A 70V/100V multi-tap transformer, with a bypass low-impedance mode, provides a solution for installed distributed music and paging application such as cafes, retail, houses of worship, theater common areas, lounges, hotels, schools and more. Included accessories such as tile rails, C-rings, cut-out templates and paint shields provide everything required for installation.

## Two-way Coaxial Ceiling Speaker

### Configuration

#### Subsystem

	Transducer	Loading
LF:	4 in. coated paper cone woofer	Vented
HF:	3/4 in. silk dome tweeter	Waveguide

#### Operating Mode

#### Amplifier Channels

Single-amp: LF/ HF

#### Signal Processing

High Pass filter

### Acoustical Performance

#### Operating Range

74 Hz to 20 kHz (-10dB)

#### Frequency Response

100 Hz to 20 kHz (+/-3dB)

#### Nominal Beamwidth

120° Conical

#### Axial Sensitivity (half space SPL)

LF/HF 87 dB

#### Maximum SPL (@ 1 m)

Average: 102 dB

Peak: 108 dB

#### Nominal Impedance

8Ω (in bypass mode)

#### Transformer Taps

70V: 3.2W, 6.3W, 12.5W, 25W

100V: 6.3W, 12.5W, 25W

#### Power Handling

60 W continuous program

### Mechanical

#### Input Connector

Removable 4-pin screw terminal with loop thru

#### Materials

Back Can: Zinc-plated Steel

Bezel material: ABS

### Weight

4.8 lbs/2.2 kg

### Dimensions

Diameter: 8 in / 203 mm

Front of Ceiling Tile to Back of Can: 7.1 in / 180 mm

Cutout Size: 7.1 in / 179 mm

### Included Accessories

- C-ring
- Tile Support Rails
- Cut-out Template
- Paint Shield
- Removable Locking Input Connector
- Grille