


HD 12-A MK5 ACTIVE TWO-WAY SPEAKER

Description	HD 12-A mk5 active speaker boosts performance with a high-power professional 12" woofer and a 1.4" HF driver, a 1400W 2ch Class-D amplifier, and innovative FiRPHASE and Bass Motion Control processing. Vocals are natural, the sound is clear at long distances, SPL power is stable at very high levels. The strength of HD series speakers comes from decades of experience building gear for the touring industry, equipping this compact cabinet with power and reliability expected for life on the road. Elegantly designed, the lightweight polypropylene cabinet with internal reinforcement offers maximum strength. The speaker also includes a steel pole mount, threaded inserts for rigging, and rubber handgrips. D-LINE offers working DJs and musicians professional sound designed with music in mind.				
Features	<ul> <li>&gt; 130 dB Max SPL</li> <li>&gt; 1400 Watts 2-way amplifier</li> <li>&gt; DSP Processing with FiRPHASE and Bass Motion Control</li> <li>&gt; 1.4" HF driver</li> <li>&gt; 12" woofer, high power, 2.5" voice coil</li> <li>&gt; 90° x 60°, wide dispersion constant directivity horn</li> <li>&gt; Silent Fan-less Class-D Amplifier</li> <li>&gt; Mylar/Ferrite driver - Kapton former coil</li> </ul>				
Part Number	13000669 HD 12-A MK5 13000684 HD 12-A MK5	220-240 V 115 V	Black Black	EAN 8024530019013 EAN 8024530019525	



HD 12-A MK5 ACTIVE TWO-WAY SPEAKER

Line Art 2D



## TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response Max SPL @ 1m Horizontal coverage angle Vertical coverage angle	45 Hz ÷ 20000 Hz 130 dB 90° 60°
Transducers	Compression Driver Woofer	1 x 1.0", 1.4" v.c 1 x 12", 2.5" v.c
Input/Output section	Input signal Input connectors Output connectors Input sensitivity Mic. Input Sensitivity	bal/unbal XLR, Jack XLR -2 dBu/+4 dBu -32 dBu
Processor section	Crossover Frequencies Protections Limiter Controls	1800 Hz Thermal, RMS Soft Limiter Volume, Boost, Mic/Line
Power section	Total Power High frequencies Low frequencies Cooling Connections	1400 W Peak, 700 W RMS 400 W Peak, 200 W RMS 1000 W Peak, 500 W RMS Convection VDE
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material Hardware Handles Pole mount/Cap Grille Color	PP Composite 1 x M10 top, 1 x M10 bottom 1 Top, 2 Side 35 mm insert Steel Black





Size	Height	647 mm / 25.47	nches	
	Width	380 mm / 14.96 i		
	Depth	380 mm / 14.96 i		
	Weight	18.3 kg / 40.34 lk	18.3 kg / 40.34 lbs	
	ACCESSORIES			
Rigging / Mounting	FLOOR STANDS			
	13360109 AC PRO-FS	Black	EAN 8024530006471	
	HORIZONTAL BRACKETS			
	13360216 H-BR 2X HD 12-32	Black	EAN 8024530011741	
	POLE MOUNT KITS			
	13360232 AC PMX		EAN 8024530010058	
	13360110 AC PRO-PM	Black	EAN 8024530006488	
	13360067 PM-KIT M20	Black	EAN 8024530014599	
Protections	COVERS			
California	13360209 CVR HD 12-32	Black	EAN 8024530010720	
Cables	CABLES KIT 13360102 AC XLR 3M3F		EAN 8024530006402	
	15500102 AC ALIC SINSI		LAN 0024330000402	